


STAK 25 (952 589)


- Allows series connection (connection of two conductors) of surge protective devices up to 25 mm²
- Allows EMC-optimised feed-through wiring according to IEC 60364-5-53



Figure without obligation



Use of STAK 25 with DEHNGuard S



Dimension drawing STAK 25

Pin-shaped terminal for EMC-optimised series connection of lightning current and surge arresters according to IEC 60364-5-53.

Type Part No.	STAK 25 952 589
Nominal voltage (a.c. / d.c.) (U_N)	600 V
Max. PV voltage (U_{CPV}) when used in combination with DEHNGuard M YPV ...	1200 V
Nominal load current (a.c.) (I_L)	100 A
Lightning impulse current (10/350 μ s)	25 kA
Discharge current (8/20 μ s)	50 kA
Rated insulation voltage (U_i)	630 V
Rated impulse withstand voltage (U_{imp})	6 kV
Operating temperature range (T_U)	-40 °C ... +80 °C
Cross-sectional area (min.)	1.5 mm ² solid / flexible
Cross-sectional area (max.)	25 mm ² stranded / 16 mm ² flexible
Type of connection	front
Suitable for	DEHNGuard S, DEHNGuard M, DEHNGap C S, DEHNshield, DK 25 feed-through terminal
Weight	17 g
Customs tariff number (Comb. Nomenclature EU)	85369010
GTIN	4013364132306
PU	4 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.