


DG S PV SCI 150 (952 551)


- Prewired modular complete unit for use in photovoltaic systems consisting of a base part and plug-in protection modules
- Combined disconnection and short-circuiting device with safe electrical isolation in the protection module (patented SCI principle)
- Tried and tested fault-resistant Y circuit



Figure without obligation



Basic circuit diagram DG S PV SCI 150



Dimension drawing DG S PV SCI 150

Modular single-pole surge arrester with three-step d.c. switching device for PV systems.

Type Part No.	DG S PV SCI 150 952 551
SPD according to EN 50539-11	type 2
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Max. PV voltage (U_{CPV})	150 V
Short-circuit current rating (I_{SCP})	10 kA
Nominal discharge current (8/20 μ s) [(DC+/DC-) $\rightarrow$ PE] (I_n)	10 kA
Max. discharge current (8/20 μ s) [(DC+/DC-) $\rightarrow$ PE] (I_{max})	20 kA
Voltage protection level (U_P)	≤ 0.8 kV
Voltage protection level at 5 kA (U_P)	≤ 0.6 kV
Response time (t_A)	≤ 25 ns
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid / flexible
Cross-sectional area (max.)	35 mm ² stranded / 25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Approvals	KEMA, UL, CSA
Weight	182 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364136687
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.