

## EB 4 F (929 095)

For 4x DG GF TV arrestersSpace-saving installationClass A product



Figure without obligation

Four-pole earthing block with F sockets for equipotential bonding of satellite cable shields or DGA GF TV lightning current arresters.

| Type                                          | EB 4 F                                         |
|-----------------------------------------------|------------------------------------------------|
| Part No.                                      | 929 095                                        |
| Max. continuous operating voltage (d.c.)      | 65 V                                           |
| Nominal current                               | 2 A                                            |
| D1 Lightning impulse current (10/350 µs)      | 10 kA                                          |
| Frequency range                               | 0-2400 MHz                                     |
| Insertion loss                                | typically 0.2 dB                               |
| Return loss                                   | ≥ 20 dB                                        |
| Shielding 30-2400 MHz (class A)               | ≥ 90 dB                                        |
| Characteristic impedance                      | 75 ohms                                        |
| Operating temperature range (T <sub>U</sub> ) | -40 °C ... +70 °C                              |
| For mounting on                               | wall                                           |
| Connection (input/output)                     | F socket / F socket                            |
| Earthing via                                  | 4x screw connection for wires up to max. Ø4 mm |
| Enclosure material                            | metal                                          |
| Colour                                        | bare surface                                   |
| Weight                                        | 90 g                                           |
| Customs tariff number (Comb. Nomenclature EU) | 85389099                                       |
| GTIN                                          | 4013364113398                                  |
| PU                                            | 1 pc(s)                                        |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.