



## FS D40 22 16 10 4500 KSV V2A (105 195)



Figure without obligation



| Type                                               | FS D40 22 16 10 4500 KSV V2A |
|----------------------------------------------------|------------------------------|
| Part No.                                           | 105 195                      |
| Total length (l1)                                  | 4500 mm                      |
| Length of tube (Ø40 x 5)                           | 2000 mm                      |
| Length of air-termination rod (Ø22 / 16 / 10) (l5) | 2500 mm                      |
| Max. free length with air-termination rod (l2)     | 4000 mm                      |
| Clamping length (l3)                               | 500 mm                       |
| Number of fixings                                  | 2                            |
| Max. gust wind speed                               | 194 km/h                     |
| Material of air-termination rod                    | StSt                         |
| Standard                                           | EN 62561-(1+2)               |
| Weight                                             | 10 kg                        |
| Customs tariff number (Comb. Nomenclature EU)      | 85389099                     |
| GTIN                                               | 4013364152090                |
| PU                                                 | 1 pc(s)                      |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Shorter transport lengths (separable pipe) are available upon request.

Special lengths of all air-termination rods / self-supporting air-termination rods are available upon request.