

## HVI LO 75 23 L100M GR M (819 136)



Figure without obligation

The HVI long Conductor for on-site assembly will be delivered in a length of 100 m on a disposable plywood reel (diameter approx. 800 mm, width approx. 485 mm) incl. one Allen key.

| Type                                                              | HVI LO 75 23 L100M GR M             |
|-------------------------------------------------------------------|-------------------------------------|
| Part No.                                                          | 819 136                             |
| Material of conductor                                             | Cu                                  |
| Material of insulation                                            | PE                                  |
| Material of sheath                                                | PE                                  |
| Colour of conductor                                               | grey •                              |
| Colour RAL                                                        | similar to 7035                     |
| Cross section of core (stranded)                                  | 19 mm <sup>2</sup>                  |
| Lightning current carrying capability (class / I <sub>imp</sub> ) | H1 / 150 kA                         |
| Equivalent separation distance s (in air)                         | ≤ 75 cm                             |
| Diameter Ø conductor                                              | 23 mm                               |
| Coating characteristics                                           | UV-stabilised and weather-resistant |
| Weight                                                            | 0 PAL/m                             |
| Customs tariff number (Comb. Nomenclature EU)                     | 85446010                            |
| GTIN                                                              | 4013364147140                       |
| PU                                                                | 100 m                               |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.