



## RD 8 STTZN R127M (800 008)



Figure without obligation

Steel wire according to EN 62561-2 with zinc coating  $\geq 50 \mu\text{m}$  on average (about  $350 \text{ g/m}^2$ ), for use as air-termination system or down conductor in lightning protection systems.

| Type                                          | RD 8 STTZN R127M                                           |
|-----------------------------------------------|------------------------------------------------------------|
| Part No.                                      | 800 008 ✓                                                  |
| Diameter Ø conductor                          | 8 mm                                                       |
| Cross-section                                 | $50 \text{ mm}^2$                                          |
| Material                                      | St/tZn                                                     |
| Standard                                      | based on EN 62561-2                                        |
| Zinc sheath                                   | $\geq 50 \mu\text{m}$ average (about $350 \text{ g/m}^2$ ) |
| Conductivity                                  | $\geq 6.66 \text{ m} / \text{Ohm mm}^2$                    |
| Resistivity                                   | $\leq 0.15 \text{ Ohm mm}^2 / \text{m}$                    |
| Weight                                        | 394 g/m                                                    |
| Customs tariff number (Comb. Nomenclature EU) | 72172030                                                   |
| GTIN                                          | 4013364018716                                              |
| PU                                            | 127 m                                                      |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Conductor materials can only be supplied in the original coil weights.

Further conductor materials as specified in the standard series EN 62561-2 are available on request.