


HVI 20M L6M SR3200 SA FSP1000 AL DBS V2A (819 371)



Figure without obligation



With internal sealing end and air-termination tip, StSt, Ø10 mm, length 1000 mm.
With tripod (Part No. 105 390) and set of threaded rods (Part No. 105 397).

Type	HVI 20M L6M SR3200 SA FSP1000 AL DBS V2A
Part No.	819 371
Material of air-termination tip	StSt
Length of air-termination tip	1000 mm
Material of supporting tube	GRP / Al
Length of supporting tube	3200 mm
Transport length	3200 mm
Outside diameter Ø	50 mm
Diameter Ø conductor	20 mm
Colour of conductor	black •
Material of conductor	Cu
RAL colour	similar to 9011
Cross-section of core (stranded)	19 mm ²
Lightning current carrying capability (class / I _{imp})	H1 / 150 kA
Equivalent separation distance s (in air)	≤ 75 cm
Material of insulation	PE
Material of sheath	PE
Material characteristics	UV-stabilised and weather resistant
Connection diameter	10 mm
Material of connection elements	StSt
Supporting tube	50 x 4 mm
Radius of tripod	600 mm
Space required for tripod	1400 x 1200 mm
Length of threaded rods	M16 x 520 mm
Minimum order length	6 m
Weight	17 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364260498
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The conductor cannot be returned as it is made to order.