


## HVI 23 L6M SR4700 SA RFS2500 AL DBS V2A (819 483)



Figure without obligation



With internal sealing end and air-termination rod Ø22 / 16 / 10 mm.

With tripod (Part No. 105 391) and set of threaded rods (Part No. 105 398).

Type	HVI 23 L6M SR4700 SA RFS2500 AL DBS V2A
Part No.	819 483
Material of air-termination tip	Al
Length of air-termination tip	2500 mm
Material of supporting tube	GRP / Al
Length of supporting tube	4700 mm
Transport length	4700 mm
Outside diameter Ø	50 mm
Diameter Ø conductor	23 mm
Colour of conductor	grey
Material of conductor	Cu
RAL colour	similar to 7035
Cross-section of core (stranded)	19 mm <sup>2</sup>
Lightning current carrying capability (class / I <sub>imp</sub> )	H1 / 150 kA
Equivalent separation distance s (in air)	≤ 75 cm
Material of insulation	PE
Material of sheath	PE
Material characteristics	UV-stabilised and weather resistant
Connection diameter	10 mm
Material of connection elements	StSt
Supporting tube	50 x 4 mm
Radius of tripod	1450 mm
Space required for tripod	2900 x 2500 mm
Length of threaded rods	M16 x 650 mm
Minimum order length	6 m
Weight	38,2 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364241978
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The conductor cannot be returned as it is made to order.